



AKFIX C108 PAINT REMOVER

1 – DESCRIPTION

Akfix C108 Paint Remover is a fast aerosol stripper which removes paint from most types of surfaces. The convenient aerosol can easily sprays hard to-reach areas and will not drip or run.

2 – PROPERTIES

- Aggressively strips even the toughest paints
- Convenient spray is easy to use
- Ease of use saves time
- No wastage due to accurate spray
- Spray gets into hard to reach areas
- Clings well to vertical surfaces
- Thick formula clings to extend contact time
- Easy clean up

3 - APPLICATIONS

- Any metallic surface with mild to heavy paint remains.
- Removes acrylics, epoxies, lacquers, adhesives, and most other automotive finishes.
- Light industrial environments
- Should not be used on fiberglass, plastics, styrene related plastics, vinyl, linoleum.

4 - INSTRUCTIONS

- Shake can vigorously before and during application.
- Due to the product's powerful stripping action, protect areas that do not require stripping.
- Hold can 15 to 20 cm from surface coating to be sprayed.
- Allow for the product to work minimum 5 min. for the paint to bubble and blister. (The time may vary depending on the type and thickness of surface coating.)
- Use a spatula and lightly scrape off the residues of paint remained.
- A second application may be necessary depending on the type, thickness and age of coating. In case of strong paint residues re-apply the product on the surface till all the old paint is removed.
- Flush surface with water or solvent and allow to dry.

NOTE : Before applying to the entire substrate, always do a test patch.



5- STORAGE AND SHELF LIFE

- Store product in the unopened container in a dry location.
- Storage information may be indicated on the product container labeling.
- Optimal Storage: 8 °C to 21 °C.
- Storage below 8 °C or greater than 28 °C can adversely affect product properties.
- 12 months if stored properly

6- RESTRICTIONS

- Pressurized container. Keep away from direct sunlight
- Keep away from sources of ignition, no smoking.
- Use only in well-ventilated areas.
- Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components.

7- PACKAGING

Product	Volume	Package
C108	200ml	24
C108	400ml	24

8- TECHNICAL PROPERTIES

Form	: Aerosol
Appearance	: Transparent
Specific gravity	: 0,972
Propellant	: Hydrocarbon
Stripping Time	: Minimum 5 min.
Shelf Life	: 12 months