



E90 ANTI-SPATTER SPRAY

1 – DESCRIPTION

Akfix E90 is an aerosol product that protects materials and surfaces in welding area against particles spattering during welding process. It ensures a perfect welding operation.

2 – PROPERTIES

- Anti-adhesion product for arc welding.
- Prevents the adhesion of “projections” on all treated surfaces.
- Suitable for protecting nozzles, weld units and tools.
- Not flammable after evaporation of solvent.

3 – APPLICATIONS

- Used in welding processes due to its ability to prevent adhesion of spattering particles to the around areas and surfaces.
- Nozzles and shrouds.
- Torches.
- Workpieces and parts.
- Jigs.
- Automatic and semi-automatic welding.
- Welding robots.

4 – INSTRUCTIONS

- Shake the aerosol vigorously before use.
- Thoroughly clean the surfaces needing treatment.
- Spray Anti-Spatter Spray evenly over the whole area from a distance of approx. 20-25cm
- Spray into the welding nozzle before starting and re-apply as required.
- Spray it approx. 10cm to the right and left of the weld so as to protect workpiece surfaces.

5 – PACKAGING

| Product | Volume | Package |
|---------|--------|---------|
| E90 | 400ml | 12 |

6- SHELF LIFE

24 Months if stored properly.

7-SAFETY

- Use gloves when working.
- Pressurized container. Do not expose to temperatures higher than +50 °C.



- Keep away from direct sunlight
- Do not pierce or burn, even after use.
- Keep away from sources of ignition, no smoking.
- Keep out of the reach of children

8- TECHNICAL PROPERTIES

| | |
|-------------------------|---------------------------|
| Form | : Aerosol |
| Appearance | : Transparent |
| Specific gravity | : 0,98 gr/cm ³ |
| Odor | : Characteristic |
| Flash Point | : N/A |