



ENAMEL SPRAY PAINT

1 – DESCRIPTION

Enamel Spray Paint is designed for quick and easy repair of irritating scratches or similar small damages on white enamel surfaces such as bath-tubs, sinks, toilet bowls, instantaneous water-heaters, and refrigerators.

2 – PROPERTIES

- High-grade acrylic quality
- For white glossy enamel surfaces
- Hard, durable surface
- Very good coverage
- Excellent adhesion
- Good flow, smooth surface
- Scratch-, shock- and impact-resistant
- Quick-drying (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat).

3– APPLICATIONS

- Suitable for quick and easy repair of irritating scratches or similar small damages on white enamel surfaces such as bath-tubs, sinks, toilet bowls, instantaneous water-heaters, and refrigerators.
- Not suitable for large-area repairs such as wash-bowls, bathtubs.

4– INSTRUCTIONS

Preparation of the ground:

- Remove loose parts, rust and dirt.
- The surface has to be clean, dry and free of fat.
- Slightly sand the damaged area and a small part of the surrounding surface.
- Remove abrasive dust.

Lacquering:

- The aerosol can should have room temperature.
- Before use shake the can vigorously for 2-3 minutes.
- Test colour of spray and compatibility of the lacquer at an invisible spot.
- Spray several thin cross-coats from a distance of approx. 25 cm.
- Do not spray over synthetic paints!



5- STORAGE AND SHELF LIFE

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).

6- ENVIRONMENT AND LABELLING

Environmentally sound: The products are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling: All products comply with the actual labelling regulations according to

Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

7- TECHNICAL PROPERTIES

Basis	: Acrylate copolymeres	
Color	: White	
Smell	: Solvent	
Degree of gloss	: Glossy, 80-85 gloss units	DIN 67530
Efficiency	: Approx. 0.8 m ² * (400 mL)	
Drying time (20 °C and 50% R.H)	: Approx. 5 minutes (Dust-dry) 2 hours (Cured) 48 hours (Resilient)	
Temperature resistance	: Up to 80°C	

* Depending on consistence and color of the ground.

8- COLOR TABLE

Art No	Color Code
423222	Enamel Spray

9- DISCLAIMER

This application-technological information is given to the best of our knowledge. The notes mentioned herein are ,however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Akkim Sealants & Adhesives is not responsible for any false usage of the product.